

iPUMP



Example picture; machine equipped with accessories

Keep your hopper full and production running with the iPump Transfer Pump. With our gentle pumping technology, your product is quickly transferred without sacrificing quality.

ADVANTAGES:

- Continuous production
- No heavy lifting required
- Simulates hand scooping gentle on your products
- Draws directly from mixing bowl or pail
- Tool free disassembly for quick and easy clean up
- Versatile fits most pails and mixing bowls
- Unique tilt mechanism allows for easy changing of mixing bowls.
- Small foot print and low height clearance
- Low air consumption

FEATURES:

- Mobile all stainless steel construction frame
- All stainless steel 50 mm piston pump
- 1,52m flexible outlet hose with end "U" pipe to hook onto the rim of a hopper - 38 mm diameter
- Flow control to adjust pump speed for different types of products
- Product photo sensor allows you to automatically keep your hopper filled to maintain a consistent product level in the depositor hopper









iPUMP



SYSTEM INCLUDES

- 2" product cylinder
- 1.5" flexible outlet hose with "U" pipe hook
- Quick start guide and spare parts kit



A perfect fit with the Multi Station



SHIPPING INFORMATION

• Dimensions: 135 cm x 97 cm x 56 cm; Weight: 60 kg



• Up to 20 litres/min.



SPEED

• Adjustable with speed control



POWER

- Air: 3 CFM at 80 psi (85 litres/min. at 5.5 bar)
- \bullet Electric: only required for optional hopper level sensor: 110 220 VAC, single phase, 1A, 50-60 Hz



PARTICLE SIZE

• Smooth products with up to 6 mm soft particulates

CERTIFICATES







Photo Sensor monitors product level in the hopper and controls the pump

